

Fresco 9000 MaXX

BEST No-Idle System



**NO-IDLE
APU^e
SLEEPER SYSTEM**



THE INDUSTRY'S ONLY
UNIVERSAL NO-IDLE SYSTEM
"INSTALLS ON ALL TRUCKS"

- **BEST** COOLING POWER
- **LOWEST** AMP. CONSUMPTION
- **SMALL & COMPACT**
- **LIGHTWEIGHT**

MODULAR COMPONENT FEATURES:

CONDENSER UNIT



- Aluminium condenser mounted on stainless steel mounting bracket
- Compact: 13 15/16" x 21 7/16" x 6 1/8" (H x W x D) - 15 lbs. 4 oz.
- Installs high on rear exterior sleeper wall for best performance
 - High durability = long life

COMPRESSOR BOX



- Scroll compressor/sealed electronics
- Compact: 8 1/4" x 8 3/4" x 14 1/4" (H x W x D) - 26 lbs.
 - Installs easily under sleeper bed
- Utilizes less undersleeper bed space than competitive systems

EVAPORATOR



- Cabinet or shelf mount unit with an easy to read digital display
- Compact & light weight: 5 5/16" x 15 3/16" x 13" (H x W x D) 11 lbs. 4 oz.
- Installed high in sleeper converting hot sleeper air into cold dry air
- Driver sets temperature - system automatically maintains temperature
- On-board system diagnostics

SANICLIMAFILTER "SCF" - OPTION

- Anti-bacterial unit removes air-borne bacteria, improving drivers' health
- Can be operated while driving or during No-Idle operation
- Service life: 40,000 hours

"2TLS" - RE-INSTALLATION KIT



"2TLS" - Kit includes all Freon replacement parts necessary for system re-installation on a second truck

AUXILIARY POWER

- DC Power**
- Available 12 DC - Power Outlet
 - Power for electronic devices

- HOTEL Power**
- Available 120 AC - Inverter (Discuss requirements with dealer for best inverter wattage)
 - Power for small appliances and electronic devices

- SHORE Power / Charging**
- Available 120 AC to 12 DC / 70 amp. Charger
 - Power for unlimited system runtime, auxiliary battery recharging and electronic devices



Fresco 9000 MaXX

INCREASES
Monthly Income

NO-IDLE FUEL SAVINGS - ONE (1) GALLON SAVED EVERY ENGINE OFF HOUR

MONTHLY IDLE HOURS	\$2.50 / gal.	\$2.75 / gal.	\$3.00 / gal.	\$3.25 / gal.
300	750.00	825.00	900.00	966.00
250	625.00	688.00	750.00	813.00
200	500.00	550.00	600.00	650.00
160	400.00	440.00	480.00	520.00

IF YOU IDLE
250 Hrs. / Month
SAVINGS CAN BE
\$750.00 / MONTH

BETTER "ROI"
VS
O.E.M SYSTEMS

"2TLS" – TWO (2) TRUCK LIFE SYSTEM

- Second truck re-installation dramatically improves **ROI**
- Ensures best system performance during second truck life
- Allows easy re-installation on different make/model of trucks

COMPETITIVE SYSTEM COMPARISON

PRODUCT	MARKET	Description	Btus	Evaporator Return Air Location	Bacteria Filter	Under Bed Space Cu. Ft.	Frame Rail Space	Condenser Bracket	*Weight Battery Pack	RCMD Alternator Amperage	System Runtime Hours	Two Truck System
		Brands										
APU	AFTERMARKET	TK	13,000	Floor	No	1.41	30"	Steel	475 Lbs.	-	Unlimited	Yes
		Carr.	12,000	Floor	No	2.60	24"	Steel	495 Lbs.	-	Unlimited	Yes
		Best System	Best Cooling		Best Health	Least Space	Lowest Space	Best Durability	Lowest Weight	Lowest Capacity	Best Run Time	Best R.O.I.
EPU - (BAC) Battery Air-Conditioning	AFTERMARKET	Fresco 9000 MaXX	9,000	Upper Sleeper	Yes	.54	0	Stainless Steel	*390 Lbs.	160+	10 - Day 15 - Night	Yes
		TK - "En"	8,000	Floor	No	2.41	20"	Steel	*572 Lbs.	270	8-10	Yes
		Carr. - "E"	10,000	Floor	No	1.05	22"	Steel	*525 Lbs.	240	8-10	Yes
		Berg. - "P"	7,500	Floor	No	2.42	0	Steel	*550 Lbs.	270/300	8-10	Yes
	OEM	Kw Peterbilt Freightliner Navistar	7,500 6,000	Floor	No	2.28	0	Steel	*485 / 550 Lbs.	270/320	8-10	No

(Above information taken from systems suppliers' publications)

SPECIFICATIONS

System Application	Class 6,7 & 8 Mid to Large size sleeper units
Truck Fitment	UNIVERSAL - All makes and models
System Run Time	10 to 15 hours (on auxiliary battery)
Refrigerant	R134a (CFC free)
Voltage	12 VDC
Max Cooling Capacity	9,000 BTUs *
Power Consumption	25 to 55 Amps. / Duty cycle hour**
Battery Protection	10.8 VDC - Low voltage disconnect
Fan Speed	Three (3) - 265 CFM
Alternator	Min. Spec. 160 Amp. - Higher amperage spec. reduces recharge time
Total Weight	System - 60 lbs. / with battery pack - 390 lbs.
2TLS	Available second truck reinstallation kit
Sleeper Air Filter New	"Saniclimafilter" removes airborne bacteria and odors within 120 minutes

* (at 89.6° F / 32° C ambient temperature) ** (STANDARD SETTINGS)



 **AUTOCLIMA**

Badge Aire, Inc.
200 East Walnut St.
Chippewa Falls, WI 54729
Ph: (715)723-7022
Email: sales@badgeaire.com
www.badgeaire.com